

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/7

THERMOSTAR SOLVENT BASED SCREEN

Revision 2

Revision date 2015-07-02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name THERMOSTAR SOLVENT BASED SCREEN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description Solvent based temperature sensitive dispersion.

1.3. Details of the supplier of the safety data sheet

Company	Thermographic Measurements Ltd
Address	Riverside Buildings Dock Road Connah's Quay Flintshire CH5 4DS United Kingdom
Web	www.t-m-c.com
Telephone	+44 (0)1244 818348
Fax	+44 (0)1244 818502
Email	sales@t-m-c.com
Email address of the competent person	chrisc@t-m-com

1.4. Emergency telephone number

Emergency telephone number +44 (0)1244 818348
Hours 09.00 to 17.00

Intended use

Manufacture of temperature-indicating products and temperature-sensitive decorative effects.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xn; R65 Xi; R43 N; R51/53 R66-67 Symbols: Xn: Harmful. N: Dangerous for the environment.
Main hazards	May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
2.1.2. Classification - EC 1272/2008	Asp. Tox. 1: H304; Skin Sens. 1: H317; Eye Dam. 1: H318; STOT SE 3: H336; Repr. 2: H361f; Aquatic Chronic 2: H411;

2.2. Label elements

Hazard pictograms



Signal Word

Danger

THERMOSTAR SOLVENT BASED SCREEN

Revision 2

Revision date 2015-07-02

2.2. Label elements

Precautionary Statement: Prevention	P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - IF exposed or concerned: Get medical advice/attention. P310 -Immediately call a POISON CENTER/doctor/ . P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P331 - Do NOT induce vomiting. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P391 - Collect spillage.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Heavy aromatic naptha solvent		64742-95-6			10 - 20%	Xn; R65 N; R51/53 R10-66-67	
Light aromatic naptha solvent		64742-95-6			10 - 20%	Xn; R65 Xi; R37 N; R51/53 R10-66-67	
4,4'-Isopropylidenediphenol	604-030-00-0	80-05-7	201-245-8		1 - 10%	Repr. Cat. 3; R62 Xi; R37-41 R43 R52	
Formaldehyde...%	605-001-00-5	50-00-0	200-001-8		0 - 0.5%	Carc. Cat. 3; R40 T; R23/24/25 C; R34 R43	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Heavy aromatic naptha solvent		64742-95-6			10 - 20%	EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411;	
Light aromatic naptha solvent		64742-95-6			10 - 20%	EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; STOT SE 3: H336; Aquatic Chronic 2: H411;	
4,4'-Isopropylidenediphenol	604-030-00-0	80-05-7	201-245-8		1 - 10%	Repr. 2: H361f; STOT SE 3: H335; Eye Dam. 1: H318; Skin Sens. 1: H317;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Seek medical attention.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

THERMOSTAR SOLVENT BASED SCREEN

Revision 2

Revision date 2015-07-02

4.1. Description of first aid measures

Ingestion	Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.
-----------	--

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin. May cause dermatitis.
Ingestion	Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Move the exposed person to fresh air. Seek medical attention.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO ₂), Dry chemical, Foam.
--	--

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

6.4. Reference to other sections

	For disposal see section 13.
--	------------------------------

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

7.3. Specific end use(s)

	Do not spray on naked flame or any other incandescent material.
--	---

THERMOSTAR SOLVENT BASED SCREEN

Revision 2

Revision date 2015-07-02

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

4,4'-Isopropylidenediphenol	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -
Formaldehyde...%	WEL 8-hr limit ppm: 2 WEL 15 min limit ppm: 2 WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: 2.5 WEL 15 min limit mg/m3: 2.5 WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Paste
Colour	Various colours according to type.
Odour	Aromatic
Flash point	>23

SECTION 10: Stability and reactivity

10.1. Reactivity

	Avoid sparks, flames, heat and sources of ignition.
--	---

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

10.5. Incompatible materials

	Oxidising agents.
--	-------------------

10.6. Hazardous decomposition products

	Burning produces obnoxious and irritating fumes.
--	--

SECTION 11: Toxicological information

THERMOSTAR SOLVENT BASED SCREEN

Revision 2

Revision date 2015-07-02

11.1.4. Toxicological Information

4,4'-Isopropylidenediphenol	Oral Rat LD50: 4240 mg/kg Dermal Rabbit LD50: 3 mL/kg	Oral Mouse LD50: 2500 mg/kg
Formaldehyde...%	Inhalation Rat LC50/2H h: 250 ppm Oral Mouse LD50: 500 mg/kg Dermal Rabbit LD50: 270 mg/kg	Oral Rat LD50: 500 mg/kg Inhalation Mouse LC50/2H h: 505 mg/m3
Heavy aromatic naptha solvent	Oral Rat LD50: 8400 mg/kg	
Light aromatic naptha solvent	Oral Rat LD50: 8400 mg/kg	

SECTION 12: Ecological information

12.1. Toxicity

4,4'-Isopropylidenediphenol	Green algae EC50/96h: 3.1 Fathead minnows LC50/96h: 4.6	Daphnia LC50/48h: 10.2
-----------------------------	--	------------------------

Further information

	An environmental hazard cannot be eliminated in the event of unprofessional handling or disposal. Do not allow product to enter drains.
--	---

SECTION 13: Disposal considerations

General information


	Dispose of in compliance with all local and national regulations.
--	---

Disposal methods

	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
--	--

SECTION 14: Transport information

Hazard pictograms

	
--	---

14.1. UN number

	UN1263
--	--------

14.2. UN proper shipping name

	PAINT
--	-------

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

THERMOSTAR SOLVENT BASED SCREEN

Revision 2

Revision date 2015-07-02

ADR/RID

Hazard ID	33
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	<p>This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.</p> <p>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p>
-------------	---

Further information

	For this product a chemical safety assessment was not carried out.
--	--

SECTION 16: Other information

Other information

Revision	<p>This document differs from the previous version in the following areas:</p> <ul style="list-style-type: none"> 1 - Description. 1 - Intended use. 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Signal Word. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Storage. 2 - Precautionary Statement: Disposal. 6 - 6.4. Reference to other sections. 12 - 12.1. Toxicity.
Text of risk phrases in Section 3	<ul style="list-style-type: none"> R10 - Flammable R23/24/25 - Toxic by inhalation, in contact with skin and if swallowed. R34 - Causes burns. R37 - Irritating to respiratory system. R40 - Limited evidence of a carcinogenic effect. R41 - Risk of serious damage to eyes. R43 - May cause sensitisation by skin contact. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52 - Harmful to aquatic organisms. R62 - Possible risk of impaired fertility. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.

THERMOSTAR SOLVENT BASED SCREEN

Revision 2

Revision date 2015-07-02

Other information

Text of Hazard Statements in Section 3	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. STOT SE 3: H335 - May cause respiratory irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Eye Dam. 1: H318 - Causes serious eye damage. Repr. 2: H361f - Suspected of damaging fertility.
---	--

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--