

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

SC350

Revision 5

Revision date 2015-07-07

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	SC350
--------------	-------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU24] Scientific research and development;
Description	Temperature indicating colour change paint.

1.3. Details of the supplier of the safety data sheet

Company	Thermographic Measurements Ltd
Address	Riverside Buildings Dock Road Connah's Quay Flintshire CH5 4DS United Kingdom
Web	www.t-m-c.com
Telephone	+44 (0)1244 818348
Fax	+44 (0)1244 818502
Email	sales@t-m-c.com
Email address of the competent person	chrisc@t-m-com

1.4. Emergency telephone number

Emergency telephone number	+44 (0)1244 818348 Hours 09.00 to 17.00
----------------------------	--

Intended use


	Temperature measurement and thermal mapping.
--	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xn; R20/21 Xi; R38 Symbols: Xn: Harmful.
Main hazards	Harmful by inhalation and in contact with skin. Irritating to skin.
2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315;

2.2. Label elements

Hazard pictograms	
Signal Word	Warning

SC350

Revision 5
Revision date 2015-07-07

2.2. Label elements

Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation.
Precautionary Statement: Prevention	P264 - Wash thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
2-methoxy-1-methylethyl acetate	607-195-00-7	108-65-6	203-603-9	01-2194759129-00	30 - 40%	R10	
Xylene	601-022-00-9	1330-20-7	215-535-7	01-2119488216-32	20 - 30%	R10 Xn; R20/21 Xi; R38	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
2-methoxy-1-methylethyl acetate	607-195-00-7	108-65-6	203-603-9	01-2194759129-00	30 - 40%	Flam. Liq. 3: H226;	
Xylene	601-022-00-9	1330-20-7	215-535-7	01-2119488216-32	20 - 30%	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Seek medical attention.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin. May cause dermatitis.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	May cause irritation to eyes. Seek medical attention if irritation or symptoms persist.
Skin contact	If you feel unwell, seek medical advice (show the label where possible).
Ingestion	If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

5.2. Special hazards arising from the substance or mixture

	. Burning produces irritating, toxic and obnoxious fumes.
--	---

SC350

Revision 5

Revision date 2015-07-07

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

6.4. Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

7.3. Specific end use(s)

Do not eat, drink or smoke in areas where this product is used or stored. Do not spray on naked flame or any other incandescent material. Ensure adequate ventilation of the working area. Restricted to professional users.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

2-methoxy-1-methylethyl acetate	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 274
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 548
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Xylene	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 220
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 441
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Approved safety goggles.

SC350

Revision 5
Revision date 2015-07-07

8.2. Exposure controls

Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.
8.2.3. Environmental exposure controls	Appropriate local exhaust ventilation is required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Red
Odour	Characteristic
Initial boiling point	140
Flash point	36
Relative density	1.1

Water solubility

	Slightly soluble in water.
--	----------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

	No data available.
--	--------------------

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

10.5. Incompatible materials

	Keep away from food, drink and animal feedingstuffs.
--	--

10.6. Hazardous decomposition products

	Burning produces obnoxious and irritating fumes.
--	--

SECTION 11: Toxicological information

11.1.4. Toxicological Information

2-methoxy-1-methylethyl acetate	Oral Rat LD50: 8532 mg/kg	Dermal Rabbit LD50: >5 gm/kg
Xylene	Inhalation Rat LC50/4H h: 5000 ppm Oral Mouse LD50: 2119 mg/kg	Oral Rat LD50: 4300 mg/kg Dermal Rabbit LD50: >1700 mg/kg

SECTION 12: Ecological information

12.2. Persistence and degradability

	No data is available on this product.
--	---------------------------------------

12.3. Bioaccumulative potential

	No data is available on this product.
--	---------------------------------------

12.4. Mobility in soil

	No data is available on this product.
--	---------------------------------------

12.5. Results of PBT and vPvB assessment

--	--

SC350

Revision 5
Revision date 2015-07-07

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

Further information

No data is available on this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of this material and its container to hazardous or special waste collection point.

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group III

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	33
Tunnel Category	(D/E)

IMDG

EmS Code F-E S-E

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355

SC350

Revision 5

Revision date 2015-07-07

IATA	
Maximum quantity	60 L
SECTION 15: Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Regulations	<p>This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.</p> <p>REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p>
15.2. Chemical safety assessment	
	For this product a chemical safety assessment was not carried out.
SECTION 16: Other information	
Other information	
Revision	<p>This document differs from the previous version in the following areas:.</p> <ul style="list-style-type: none"> 1 - Product Use. 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Signal Word. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 12 - 12.1. Toxicity.
Text of risk phrases in Section 3	<p>R10 - Flammable</p> <p>R20/21 - Harmful by inhalation and in contact with skin.</p> <p>R38 - Irritating to skin.</p>
Text of Hazard Statements in Section 3	<p>Flam. Liq. 3: H226 - Flammable liquid and vapour.</p> <p>Acute Tox. 4: H312 - Harmful in contact with skin.</p> <p>Skin Irrit. 2: H315 - Causes skin irritation.</p> <p>Acute Tox. 4: H332 - Harmful if inhaled.</p>
Further information	
	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. All components TSCA compliant.</p> <p>All components are TSCA compliant.</p>
HMIS LABELLING	HEALTH 1, FLAMMABILITY 3, PHYSICAL HAZARD 1. PERSONAL PROTECTION: G.